

~~14~~ 16. (Amended) Polyethylene-based composition for the manufacture of pipes and pipe couplings according to Claim 1, wherein talc is added in an amount effective to increase a creep resistance of said pipes and pipe couplings made of said composition.

E1 ~~13~~ 17. (Amended) The polyethylene-based composition for the manufacture of pipes and pipe couplings of Claim ~~13~~ 15, wherein talc is added in an amount effective to increase a creep resistance of said pipes and pipe couplings made of said composition.

~~16~~ 18. (amended) A pipe or a pipe coupling comprising the composition of Claim 1.

no. 11/10/01 ~~17~~ 19. (amended) A pipe or a pipe coupling comprising the composition of Claim 3. ~~17~~ 19

E2 ~~18~~ 20. (Amended) The composition of Claim 1, wherein the composition is in the form of a shaped article characterized by creep resistance (t), wherein t = creep resistance expressed in terms of time to fracture, measured according to ISO Standard 1167 (1996) at 20° C on a pipe having a diameter of 50 mm and a thickness of 3 mm and under a circumferential stress of 12.4.

~~19~~ 21. (Amended) The composition of Claim 3, wherein the composition is in the form of a shaped article characterized by creep resistance (t), wherein t = creep resistance expressed in terms of time to fracture, measured according to ISO Standard 1167 (1996) at 20° C on a pipe having a diameter of 50 mm and a thickness of 3 mm and under a circumferential stress of 12.4.

~~20~~ 22. (Amended) The pipe or pipe coupling of Claim ~~18~~ 16, which is characterized by creep resistance (t), wherein t = creep resistance expressed in terms of time to fracture, measured according to ISO Standard 1167 (1996) at 20° C on a pipe having a diameter of 50 mm and a thickness of 3 mm and under a circumferential stress of 12.4.

21
23. (Amended) The pipe or coupling of Claim 19, which is characterized by creep resistance (t), wherein t = creep resistance expressed in terms of time to fracture, measured according to ISO Standard 1167 (1996) at 20° C on a pipe having a diameter of 50 mm and a thickness of 3 mm and under a circumferential stress of 12.4.

Please add the following Claims:

22
24. The pipe or pipe coupling of Claim 18, wherein the polyethylene is high density polyethylene.—

23
25. The pipe or pipe coupling of Claim 19, wherein the polyethylene is high density polyethylene.--